

Features

- Single cylindrical handle allows for both volume and temperature control
- Temperature memory allows faucet to be turned on and off at any temperature setting.
- Includes pop-up drain with 1-1/4" tailpiece
- KOHLER ceramic disc valves exceed industry longevity standards for a lifetime of durable performance
- 1.2 gal/min (4.5 l/min) maximum flow rate [max at 60 psi (4.1 bar)]
- 7-1/8" spout reach.
- Ideal for vessel sink applications
- Coordinates with Composed faucets, accessories, and showering components to complete your bathroom.

Material

- Premium Metal Construction
- KOHLER® finishes resist corrosion and tarnish

Installation

- Single-hole mounting
- Pre-attached flexible supply lines simplify installation



ADA

Codes/Standards



ASME A112.18.1/CSA B125.1
NSF/ANSI 61
NSF/ANSI 372
All applicable US Federal and State material regulations
DOE - Energy Policy Act 1992
EPA WaterSense®
California Energy Commission (CEC)
ADA
ICC/ANSI A117.1


KOHLER® Faucet Lifetime Limited Warranty

See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.

Color	Code	Description
	CP	Polished Chrome
	TT	Titanium



Technical Information

All product dimensions are nominal.

Faucet:

Flow rate:	1.2 gal/min (4.5 l/min)
Pressure:	60 psi (4.1 bar)
Valve body:	Cast brass
Drain with overflow:	Yes
Drain tailpiece included:	Yes

Spout:

Spout reach:	7-1/8" (181 mm)
--------------	-----------------

Notes

Install this product according to the installation guide.

ADA compliant when installed to the specific requirements of these regulations.