KOHLER_®

Features

- Anodized aluminum construction with a durable rust-free and chip-free finish.
- Two adjustable tempered-glass shelves.
- Full-overlay mirrored door with beveled edges.
- Mirrored interior.
- Two-way adjustable hinges with 108-degree opening capability for easy cabinet access.
- Can be installed with left- or right-hand swing.
- Includes mounting hardware for surface or recessed installation.
- Includes side mirror kit for surface mount installation.

Material

Anodized aluminum.

Recommended Products/Accessories

K-2659 Cabinet Lockbox K-2958 Audio Add-on



Codes/Standards

None Applicable

KOHLER[®] One-Year Limited Warranty


See website for detailed warranty information.




Medicine Cabinet K-CB-CLC2026FS



Medicine Cabinet K-CB-CLC2026FS





Technical Information

All product dimensions are nominal.

Recess-Mount Cutout:

| Width: | 19-1/4" (489 mm) |
|---------|------------------|
| Height: | 25-1/4" (641 mm) |
| Depth: | 3-5/8" (92 mm) |

Notes

Install this product according to the installation guide.

CAUTION: Risk of electric shock. Electrical wiring may need to be relocated.

IMPORTANT! For recess mounting, the wall cavity must be framed and cabinet secured to framing studs. Reroute any electrical wires or water supply piping from the wall cavity. If you encounter drain or vent piping, or if your wall is load-bearing, consult a professional before proceeding.

CAUTION: Risk of property damage. For surface mounting, use anchors (not provided) rated for the loaded weight of this product. Refer to the anchor manufacturer's instructions.

When determining the height of the cabinet, ensure the mirrored door will clear all obstacles (such as a faucet). A minimum distance of 3 " (76 mm) is required.

Roughing-in opening for recess-mount installations: 19-1/4" (362 mm) x 25-1/4" (641 mm) x 3-5/8" (92 mm).

