

Rite-Temp[®] bath and shower trim set, no valve K-TS16225-4

Features

- Single level handle controls both on/off activation and temperature setting.
- Showerhead features MasterClean[™] sprayface for easy cleaning.
- Provides temperature regulation and automatic anti-scald protection.
- Trim set requires valve to complete installation (sold separately).
- Coordinates with Margaux faucets and accessories.
- Includes single function 2.5 gpm (9.5 l/min) showerhead with Katalyst[®] Air Induction Technology.
- Includes diverter bath spout with 1/2" NPT connection.
- Includes faceplate with ADA-compliant metal level handle.
- Includes shower arm and flange.
- Includes valve trim, bath spout, showerarm with flange, and showerhead.
- THIS NEW K-TS16225-3 TRIM REPLACES THE EXISTING K-T16225-3 TRIM. THE NEW TRIM IS IDENTICAL AND INCLUDES TRIM ADAPTER KITS FOR BOTH RITE-TEMP K-304/K-2971 HIFLOW AND THE NEW K-8304 SERIES VALVE.

Material

Premium material construction with metal handle ensures reliability and durability.

Technology

 Pressure-balancing diaphragm technology maintains outlet temperature within +/-3 degrees Fahrenheit during water pressure fluctuations.

Installation

- Bath- or deck-mount.
- Trim set requires valve to complete installation (sold separately).

Required Products/Accessories

- K-304/K-P304 Series Rite-Temp® Valves
- or

K-8304/K-P8304 Series Rite-Temp® Valve & Cartridge Kits or

K-8300/K-P8300 Series Rite-Temp® Valve Body Rough-ins K-8305/K-P8305 Series Rite-Temp® Cartridges

or

K-2971-KS 3/4" Pressure-balancing Valve

Recommended Products/Accessories

K-23723 Faucet cleaner

Optional Products/Accessories

K-10350 Deep Rough-In Kit For K-8305 Cartridges K-10351 Test Cap For K-8300 Series Valve Bodies







Codes/Standards

ASME A112.18.1/CSA B125.1 DOE - Energy Policy Act 1992

KOHLER[®] Faucet Lifetime Limited Warranty

See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.

Color Code Description

CP	Polished Chrome
SN	Vibrant® Polished Nickel
AF	Vibrant® French Gold
D N1	


- BN Vibrant® Brushed Nickel
- BV Vibrant® Brushed Bronze



Margaux®



Rite-Temp® bath and shower trim set, no valve K-TS16225-4



Technical Information

All product dimensions are nominal. Drain included: No

Showerhead/Body Spray:

Rated maximum flow:2.5 gal/min (9.5 l/min)Pressure:80 psi (5.5 bar)

Notes

Install the product according to the installation guide.

NOTICE: Risk of product damage. Long screws, for installing trim, can damage the K-2971-KS valve. Consult the trim installation guide to verify if the thin wall installation kit (88526) is needed. Install straight pipe or tube drop of 7" (178 mm) to 18" (457 mm) with single elbow between the

to 18" (457 mm) with single elbow between the valve and wall-mount spout.

